
2-channel differential thermometer with display and connections for radio sensor

LM8575

1

The differential thermometer records temperature values from 2 connected thermocouple probes, and displays these values simultaneously. Readings from an additional temperature sensor transmitted in wireless mode, i.e. via radio, can be displayed additionally on the testo 922 measuring device.

The temperature difference can be invoked directly. Current measurement data such as max./min. values can be printed out on location using Testo quick printer. During cyclic printing, measured data can be additionally output once per minute, for instance.

Functions:

- Display of differential temperature
- Cyclical printout of readings, e.g. once per minute
- Continuous display of max./min. values
- Hold-button for retaining measured values
- Display lighting
- On-site printing with a Testo quick printer (optional)

Technical data:

- Operating temperature: -20 ... +50°C
- Housing material: ABS
- Storage temperature: -40 ... +70°C
- Battery type: 9V block, 6F22
- Dimensions: 182 x 64 x 40mm
- Weight: 1.0kg



TopSafe protective sheath for 2-channel differential thermometer

LM8576

1

TopSafe, an indestructible case providing protection against dirt and impact



Type K surface sensor with extra-wide measuring probe, waterproof

LM8577

1

Extremely fast-acting surface probe with a resilient thermocouple strip, also for uneven surfaces; short-term measurement range to +500°C, type K thermocouple

Technical data:

- Measuring range: -60 ... +400°C
- Sensor tube length: 115mm
- Sensor tube diameter: Ø 5mm
- Response time: 30sec
- Cable length: 1.2 m
- Accuracy class: 2
- Connection cable: Fixed, stretched



Type K pipe-contact sensor with interchangeable measuring probes for 5..65-mm pi

LM8578

1

Technical data:

Measuring range: -60 ... +130°C

Response time: 5 sec

Cable length: 1.2 m

Accuracy class: 2

Connection cable: Fixed, stretched



Manometer battery with storage case and filling hose

LM8582

1

The 4-way manometer array is used to measure and adjust pressures in refrigeration systems. The manometer array is suitable for a variety of refrigerants. The low-pressure elements are marked blue, the high-pressure elements are marked red.

Technical data:

- Includes: 4-way manometer array, case, 3 hoses
- Mounting: Suspended
- Manometer: 2 units, oil-filled
- Class 1a
- Scale: R134a
- Hoses: 90cm
- Connections: 7/16" UNF red, black and blue, 5/8" UNF yellow
- Weight: 2.0 kg



Materials for attachment and assembly

This set consists of consumable materials in sufficient quantity to provide for all the needs of a single work station over a period of two years.

set of copper pipes, various widths, for project assembling (2 places)	SE2675-1H	1
---	-----------	---

Pipe connector set for components with flare fittings	SE2675-2P	1
--	-----------	---

The set consists of the following:
 This set is sufficient for 1 work station

- 40 x Lock nuts, 7/16"
- 40 x Lock nuts, 5/8"
- 30 x Lock nuts, 3/4"
- 20 x Lock nuts, 7/8"
- 3 x Double nuts, DM, 7/16"
- 3 x Double nuts, DM, 5/8"
- 3 x Double nuts, DM, 3/4"
- 2 x Double nuts, DM, 7/8"
- 20 x Sealing caps, DK, 7/16"
- 20 x Sealing caps, DK, 5/8"
- 20 x Sealing caps, DK, 3/4"
- 20 x Sealing caps, DK, 7/8"
- 20 x Sealing rings, DR, 7/16"
- 20 x Sealing rings, DR, 5/8"
- 20 x Sealing rings, DR, 3/4"
- 20 x Sealing rings, DR, 7/8"
- 3 x Connectors, VN, 7/16"
- 3 x Connectors, VN, 5/8"
- 3 x Connectors, VN, 3/4"
- 3 x Connectors, VN, 7/8"
- 3 x Connectors, VR, 5/8"-7/16"
- 3 x Connectors, VR, 3/4"-7/16"
- 3 x Connectors, VR, 3/4"-5/8"
- 3 x Connectors, VR, 7/8"-5/8"
- 3 x Connectors, VR, 7/8"-3/4"
- 2 x Schrader T-joints, 7/16"
- 1 x Cylinder connector, FA, 774 305
- 3x T-joints, TN, 7/16"
- 3 x T-joints, TN, 5/8"
- 3 x T-joints, TN, 3/4"
- 3 x T-joints, TN, 7/8"
- 3 x T-joints, TR, 5/8"-7/8"
- 3 x T-joints, TR, 7/8"-5/8"
- 3 x Screw nozzles, AS, 7/16"-5/8"
- 3 x Screw nozzles, AS, 7/16"-3/4"
- 3 x Screw nozzles, AS, 5/8"-3/4"



Set of fasteners for pipes on component bases

SE2675-2N

1

The set consists of the following items:

- 1 x Set of pipe clips, DM, set of 25, 6 A€
- 1 x Set of pipe clips, DM, set of 25, 10 A€
- 1 x Set of pipe clips, DM, set of 25, 12 A€
- 1 x Set of pipe clips, DM, set of 25, 15 A€
- 25 x House pipe clips, MP-LHI 8-12 M8
- 25 x House pipe clips, MP-LHI 12-16 M8
- 4 x House pipe clips for pressure regulator, MP-LHI 25-31 M8
- 2 x House pipe clips for filter dryer, MP-LHI 38-55 M8
- 25 x Threaded pieces, M8x30
- 25 x Threaded pieces, M8x40
- 25 x Threaded pieces, M8x60
- 12 x Threaded pieces, M8x80
- 100 x M8 nuts
- 150 x Washers M8 8.4x16
- 50 x Hex screws, M6x12
- 18 x Threaded pieces, M6x12
- 12 x Threaded pieces, M6x50
- 12 x Threaded pieces, M6x70
- 50 x M6 nuts
- 100 x Washers M6 6.4x12
- 6 x Spacer collar, M6 x 30 mm
- 4 x Vibration plate, MP-2-C



Set of 25 fasteners for wires and components

SE2675-2M

1

The set consists of the following items:

- 25 x Assembly racks for holes in 8.5/6.5 grid wall panel
- 5 x Assembly racks for holes in 8.5/6.5 grid wall panel

